

NAS CLOSE TOLERANCE SHEAR 5/16" (5/16-24TPI) BOLT

E-Mail: sales@asapspares.com.au

227



NAS CLOSE TOLERANCE BOLT

UN-DRILLED SHANK SHEAR BOLT (5/16-24 TPI TPI)

OUR PART NUMBER	DESCRIPTION UN-DRILLED SHANK	Grip	Length
NAS6205-4	BOLT CLOSE TOLERANCE	.250"	.573"
NAS6205-6	BOLT CLOSE TOLERANCE	.375"	.698"
NAS6205-7	BOLT CLOSE TOLERANCE	.438"	.761"
NAS6205-8	BOLT CLOSE TOLERANCE	.500"	.823"
NAS6205-9	BOLT CLOSE TOLERANCE	.562"	.885"
NAS6205-10	BOLT CLOSE TOLERANCE	.625"	.948"
NAS6205-11	BOLT CLOSE TOLERANCE	.688"	1.011"
NAS6205-12	BOLT CLOSE TOLERANCE	.750"	1.073"
NAS6205-13	BOLT CLOSE TOLERANCE	.813"	1.135"
NAS6205-14	BOLT CLOSE TOLERANCE	.875"	1.198"
NAS6205-15	BOLT CLOSE TOLERANCE	.938"	1.261"
NAS6205-16	BOLT CLOSE TOLERANCE	1.000"	1.323"
NAS6205-19	BOLT CLOSE TOLERANCE	1.188"	1.511"
NAS6205-20	BOLT CLOSE TOLERANCE	1.250"	1.573"
NAS6205-21	BOLT CLOSE TOLERANCE	1.312"	1.635"
NAS6205-22	BOLT CLOSE TOLERANCE	1.375"	1.698"
NAS6205-25	BOLT CLOSE TOLERANCE	1.562"	1.885"
NAS6205-28	BOLT CLOSE TOLERANCE	1.750"	2.073"
NAS6205-29	BOLT CLOSE TOLERANCE	1.813"	2.135"
NAS6205-30	BOLT CLOSE TOLERANCE	1.875"	2.198"
NAS6205-31	BOLT CLOSE TOLERANCE	1.938"	2.261"
NAS6205-32	BOLT CLOSE TOLERANCE	2.000"	2.323"
NAS6205-34	BOLT CLOSE TOLERANCE	2.125"	2.448"
NAS6205-36	BOLT CLOSE TOLERANCE	2.250"	2.573"
NAS6205-38	BOLT CLOSE TOLERANCE	2.375"	2.698"
NAS6205-40	BOLT CLOSE TOLERANCE	2.500"	
NAS6205-42	BOLT CLOSE TOLERANCE	2.625"	
NAS6205-44	BOLT CLOSE TOLERANCE	2.375"	
NAS6205-46	BOLT CLOSE TOLERANCE	2.500"	
NAS6205-51	BOLT CLOSE TOLERANCE	3.188"	

NAS CLOSE TOLERANCE BOLT

DRILLED SHANK SHEAR BOLT (5/16-24 TPI TPI)

OUR PART NUMBER	DESCRIPTION DRILLED SHANK	Grip	Length
NAS6205D-11	CLOSE TOLERANCE DRILLED	.688"	1.011"
NAS6205D-13	CLOSE TOLERANCE DRILLED	.813"	1.135"
NAS6205D-14	CLOSE TOLERANCE DRILLED	.875"	1.198"
NAS6205D-17	CLOSE TOLERANCE DRILLED	1.062"	1.385"

NAS CLOSE TOLERANCE SHEAR 5/16" (5/16-24TPI) BOLT

E-Mail: sales@asapspares.com.au

227

OUR PART NUMBER	DESCRIPTION DRILLED SHANK	Grip	Length
NAS6205D-18	CLOSE TOLERANCE DRILLED	1.125"	1.448"
NAS6205D-19	CLOSE TOLERANCE DRILLED	1.188"	1.511"
NAS6205D-22	CLOSE TOLERANCE DRILLED	1.375"	1.698"
NAS6205D-23	CLOSE TOLERANCE DRILLED	1.438"	1.761"
NAS6205D-24	CLOSE TOLERANCE DRILLED	1.500"	1.823"
NAS6205D-25	CLOSE TOLERANCE DRILLED	1.562"	1.885"
NAS6205D-28	CLOSE TOLERANCE DRILLED	1.750"	2.073"
NAS6205D-30	CLOSE TOLERANCE DRILLED	1.875"	2.198"
NAS6205D-42	CLOSE TOLERANCE DRILLED	2.625"	
NAS6205D-46	CLOSE TOLERANCE DRILLED	2.500"	
NAS6205D-51	CLOSE TOLERANCE DRILLED	3.188"	

All measurements are Imperial